

SC ステンレス製	ねじの呼び	全長 (mm)	ネジ長さ (mm)	最大取付物厚 (mm)	ドリル径 (mm)	埋込長さ (mm)	穿孔深さ (mm)	入数		最大引張強度 (kN)
								小箱 (本)	大箱 (本)	
SC-645	M6	45	15	6	6.4	30	36 以上	50	800	4.5
SC-660		60	20	21						
SC-850	M8	50	20	9	8.5	30	38 以上	50	400	12.5
SC-860		60		19						
SC-870		70	25	29						
SC-880		80	30	39						
SC-890		90		49						
SC-810		100	35	61						
SC-1050		M10	50	20						
SC-1060	60		12							
SC-1070	70		25	22						
SC-1080	80		30	32						
SC-1090	90			42						
SC-1010	100		52							
SC-1012	120		72							
SC-1260	M12	60	25	9	12.7	45	57 以上	30	180	21.0
SC-1270		70		19						
SC-1280		80	30	29						
SC-1290		90		39						
SC-1210		100	35	59						
SC-1212		120		89						
※ SC-1215		150	89							
SC-1680	M16	80	40	10	17.0	60	76 以上	15	90	31.1
SC-1610		100		20						
SC-1612		120		40						
※ SC-1615		150		70						
※ SC-1619		190		110						
※ SC-2013	M20	130	50	25	21.5	80	100 以上	10	40	37.7
※ SC-2015		150		45						
※ SC-2019		190		85						
SC-3060	W3/8	60	25	11	10.0	35	45 以上	50	400	11.4
SC-4070	W1/2	70		9	12.7	45	57 以上	30	240	16.1

※はストレートピンになります。

※ M6 ~ M16・W3/8 は座付きナット仕様
M20・W1/2 はナット・ワッシャ仕様

※引張強度は、社内試験値を表示しています。

溶融亜鉛メッキ (ドブメッキ)

DC スチール製	ねじの呼び	全長 (mm)	ネジ長さ (mm)	最大取付物厚 (mm)	ドリル径 (mm)	埋込長さ (mm)	穿孔深さ (mm)	入数		最大引張強度 (kN)
								小箱 (本)	大箱 (本)	
DC-850	M8	50	20	9	8.5	30	38 以上	50	800	8.6
DC-870		70	25	29					400	
DC-1050	M10	50	20	7	10.5	35	45 以上	50	400	14.6
DC-1060		60		12						
DC-1070		70	25	22						
DC-1080		80	30	32						
DC-1010		100		52						
DC-1260		M12	60	25					9	
DC-1270	70		19							
DC-1280	80		30	29						
DC-1290	90			39						
DC-1210	100		50	59						
DC-1212	120			120						
DC-1610	M16	100	40	20	17.0	60	76 以上	15	90	24.2
DC-1612		120		40						
DC-1615		150		70						