



JCAA 認証商品 

電気亜鉛メッキ (クロメート処理)

■特長

プラグアンカーは施工後、仕様によりボルトを選定できるので、様々な用途に使用できます。施工後のアンカーは他の機材等の妨げになりません。

■用途

建設工事・電気工事・冷暖房工事・看板工事・間仕切り工事・屋根工事・機械設置工事等プラグアンカーはあらゆる工事に使用されています。

PA スチール製	ねじの呼び	外径 (mm)	全長 (mm)	ネジ長さ (mm)	ドリル径 (mm)	埋込長さ (mm)	穿孔深さ (mm)	入数		打込棒品番	最大引張強度 (kN)
								小箱 (本)	大箱 (本)		
PA-6M	M6	10.5	30	11	11.0	30	33	200	1000	PAT-20	11.3
PA-8M	M8	12.0	35	13	12.5	35	38	150	750	PAT-25	16.5
 PA-10M	M10	14.0	40	16	14.5	40	45	100	500	PAT-30	19.7
 PA-12M	M12	17.5	50	22	18.0	50	55	50	250	PAT-40	31.9
PA-12ML			80	25		80	85	30	150		34.7
 PA-16M	M16	21.5	60	25	22.0	60	65	25	125	PAT-50	45.1
PA-20M	M20	25.4	80	35	26.0	80	90	15	75	PAT-60	59.2
PA-22M	M22	28.5	90	39	29.0	90	100			PAT-70	74.1
PA-24M	M24	31.8	110	50	33.0	110	120	8	40	PAT-80	77.6
PA-25	W5/16	12.0	35	13	12.5	35	38	150	750	PAT-25	15.2
 PA-30	W3/8	14.0	40	16	14.5	40	45	100	500	PAT-30	25.0
PA-30S			35	13		35	38	150	750	PAT-30S	19.3
PA-30SS			30	11		30	33				14.9
 PA-40	W1/2	17.5	50	22	18.0	50	55	50	250	PAT-40	32.2
PA-40L			80	25		80	85	30	150		34.7
PA-50	W5/8	21.5	60	25	22.0	60	65	25	125	PAT-50	38.5

SPA ステンレス製	ねじの呼び	外径 (mm)	全長 (mm)	ネジ長さ (mm)	ドリル径 (mm)	埋込長さ (mm)	穿孔深さ (mm)	入数		打込棒品番	最大引張強度 (kN)
								小箱 (本)	大箱 (本)		
SPA-6M	M6	10.5	30	13	11.0	30	33	200	1000	PAT-20	14.1
 SPA-8M	M8	12.0	35	13	12.5	35	38	150	750	PAT-25	16.8
 SPA-10M	M10	14.0	40	15	14.5	40	45	100	500	PAT-30	26.1
 SPA-12M	M12	17.5	50	21	18.0	50	55	50	250	PAT-40	34.6
 SPA-16M	M16	21.5	60	23	22.0	60	65	25	125	PAT-50	41.2
SPA-20M	M20	25.4	80	36	26.0	80	90	15	75	PAT-60	64.3
SPA-22M	M22	28.5	90	39	29.0	90	100	15	75	PAT-70	76.7
SPA-24M	M24	31.8	110	50	33.0	110	120	8	40	PAT-80	77.4
SPA-30	W3/8	14.0	40	15	14.5	40	45	100	500	PAT-30	21.3
SPA-30S	W3/8	12.0	35	13	12.5	35	38	150	750	PAT-30S	19.8
SPA-40	W1/2	17.5	50	21	18.0	50	55	50	250	PAT-40	33.9

溶融亜鉛メッキ (ドブメッキ)

DPA スチール製	ねじの呼び	外径 (mm)	全長 (mm)	ネジ長さ (mm)	ドリル径 (mm)	埋込長さ (mm)	穿孔深さ (mm)	入数		打込棒品番	最大引張強度 (kN)
								小箱 (本)	大箱 (本)		
DPA-8M	M8	12.0	35	13	12.5	35	38	150	750	PAT-25	16.5
DPA-10M	M10	14.0	40	16	14.5	40	45	100	500	PAT-30	19.7
DPA-12M	M12	17.5	50	22	18.0	50	55	50	250	PAT-40	31.9
DPA-16M	M16	21.5	60	25	22.0	60	65	25	125	PAT-50	45.1
DPA-20M	M20	25.4	80	35	26.0	80	90	15	75	PAT-60	59.2
DPA-22M	M22	28.5	90	39	29.0	90	100	15	75	PAT-70	74.1
DPA-24M	M24	31.8	110	50	33.0	110	120	8	40	PAT-80	77.6